## **Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

1. (Currently Amended) A fiber mat for use in a building material, said mat comprising:

a plurality of fibers;

a <u>an aqueous</u> resinous fiber binder, said fibers fixedly distributed in said binder; and

a water-based urethane modifier wherein the weight ratio of said fiber binder to said urethane modifier is between about 200:1 to about 4:1.

- 2. (Original) The fiber mat of Claim 1, wherein said urethane modifier comprises a polyurethane modifier.
- 3. (Original) The fiber mat of Claim 2, wherein said polyurethane modifier is selected from the group consisting of: an aliphatic polyurethane, an aromatic polyurethane, and a hybrid polyurethane.
- 4. (Original) The fiber mat of Claim 1, wherein said fiber binder comprises a formaldehyde type binder.
  - 5. (Original) The fiber mat of Claim 4, wherein said formaldehyde type binder is

selected from the group consisting of: a urea/formaldehyde binder, a phenol/formaldehyde binder, and a melamine/formaldehyde binder.

- 6. (Previously Presented) The fiber mat of Claim 1, wherein the weight ratio of said fiber binder to said urethane modifier is between about 99:1 to about 9:1.
- 7. (Original) The fiber mat of Claim 1, said mat containing from about 55 wt.% to about 98 wt.% fiber and from about 0.05 wt.% to about 45 wt.% fiber binder.
- 8. (Original) The fiber mat of Claim 1, wherein said fibers comprise glass fibers.
- 9. (Original) The fiber mat of Claim 1, said mat containing from about 55 wt.% to about 98 wt.% glass fiber and from about 15 wt.% to about 30 wt.% fiber binder.
- 10. (Original) The fiber mat of Claim 1, further comprising an asphalt coating on at least one surface of said mat, said mat having a tensile strength greater than about 1,000 psi.
- 11. (Currently Amended) A fibrous mat roofing shingle, comprising:a plurality of glass fibers; and

a fixative composition comprising a <u>an aqueous</u> fiber binder and a water based polyurethane modifier wherein the weight ratio of said fiber binder to said polyurethane modifier is between about 200:1 to about 4:1,

wherein said fibers are fixedly distributed in said fixative composition.

DC01/COULJ/376119.1

- 12. (Original) The fibrous mat of Claim 11, wherein the concentration of the fiber binder, based on the weight of the fibrous mat, is in the range of from about 0.05 wt.% and about 45 wt.%.
- 13. (Original) The fibrous mat of Claim 11, wherein said glass fibers comprise a plurality of glass filaments having an average length of from about 1/4 to about 3 inches and a diameter of from about 1 to about 50 microns.
- 14. (Original) The fibrous mat of Claim 11, wherein the concentration of said glass filaments is between about 55 and about 98 wt.%.
- 15. (Original) The fibrous mat of Claim 11, wherein said polyurethane modifier is selected from the group consisting of: an aliphatic polyurethane, an aromatic polyurethane, and a hybrid polyurethane.
- 16 20. canceled
- 21. (Previously Presented) The fibrous mat of Claim 11, wherein the weight ratio of said fiber binder to said polyurethane modifier is between about 99:1 to about 9:1.
- 22. canceled